



PATTON & COOKE SPLIT STRAIN RELIEF ENTRANCE FITTINGS



The split strain relief entrance fitting is ideally suited for installation where trailing cable couplers are not being used, but where cables may be installed and removed frequently. The split design means that the entrance fitting can be installed or removed without disturbing the stress cones, sleeves or taping which makes up the cable termination. Cables can be installed and removed quickly. The strain relief entrance fitting is tightened to provide a positive clamp on the cable. No tools are required. Pilot holes are provided on the flange to permit field drilling and fastening of the strain relief fitting to the enclosure. Split strain relief entrance fittings are available in many sizes, which cover cable outside diameters from 1.76"-3.5" (44.7 mm - 88.9 mm).

Outside Cable Diameter		Patton & Cooke Catalogue Number
(mm)	(in)	
44.7-47.5	1.76-1.87	11W-040-D-L
47.8-50.8	1.88-2.00	11W-040-D-M
51.1-53.8	2.01-2.12	11W-040-D-N
54.1-57.2	2.13-2.25	11W-040-D-P
57.4-60.2	2.26-2.37	11W-040-D-Q
60.5-63.5	2.38-2.50	11W-040-D-R
63.8-66.5	2.51-2.63	11W-040-D-S
66.8-69.9	2.64-2.75	11W-040-D-T
70.1-72.9	2.76-2.87	11W-040-D-U
73.2-76.2	2.88-3.00	11W-040-D-V
76.5-79.2	3.01-3.12	11W-040-D-W
79.5-82.6	3.13-3.25	11W-040-D-X
82.8-85.6	3.26-3.37	11W-040-D-Y
85.9-88.9	3.38-3.50	11W-040-D-Z
44.7-47.5	1.76-1.87	11W-040-E-L c/w drilled flange holes
47.8-50.8	1.88-2.00	11W-040-E-M c/w drilled flange holes
51.1-53.8	2.01-2.12	11W-040-E-N c/w drilled flange holes
54.1-57.2	2.13-2.25	11W-040-E-P c/w drilled flange holes
57.4-60.2	2.26-2.37	11W-040-E-Q c/w drilled flange holes
60.5-63.5	2.38-2.50	11W-040-E-R c/w drilled flange holes
63.8-66.5	2.51-2.63	11W-040-E-S c/w drilled flange holes
66.8-69.9	2.64-2.75	11W-040-E-T c/w drilled flange holes
70.1-72.9	2.76-2.87	11W-040-E-U c/w drilled flange holes
73.2-76.2	2.88-3.00	11W-040-E-V c/w drilled flange holes
76.5-79.2	3.01-3.12	11W-040-E-W c/w drilled flange holes
79.5-82.6	3.13-3.25	11W-040-E-X c/w drilled flange holes
82.8-85.6	3.26-3.37	11W-040-E-Y c/w drilled flange holes
85.9-88.9	3.38-3.50	11W-040-E-Z c/w drilled flange holes

For other outside cable diameters, or for variations to the design, contact Patton & Cooke Co.



High Voltage Equipment Solutions. Design and Manufacturing.

We make the connection.